

Environmental Product Declaration

According to EN15804+A2

This declaration is for: **SPC WALL PANEL**

Provided by: Prodinex BV



MRPI® registration 1.1.00811.2025

program operator Stichting MRPI® publisher Stichting MRPI® www.mrpi.nl date of first issue **24-4-2025** date of this issue **24-4-2025** expiry date **24-4-2030**







COMPANY INFORMATION

Prodinex BV Ommelseweg 67 5721 WT Asten Netherlands +31 (0)493 67 17 00 info@prodinex.com https://www.prodinex.com/

MRPI® REGISTRATION

1.1.00811.2025

DATE OF THIS ISSUE

24-4-2025

EXPIRY DATE

24-4-2030

SCOPE OF DECLARATION

This MRPI®-EPD certificate is verified by Gert-Jan Vroege, Eco-intelligence. The LCA study has been done by Bram Klerkx, SGS INTRON. The certificate is based on an LCA-dossier according to EN15804+A2. It is verified according to the 'MRPI®-EPD verification protocol November 2020.v4.0'. EPDs of construction products may not be comparable if they do not comply with EN15804+A2. Declaration of SVHC that are listed on the 'Candidate list of Substances of Very High Concern for authorisation' when content exceeds the limits for registration with ECHA.

PRODUCT

SPC WALL PANEL

DECLARED UNIT / FUNCTIONAL UNIT

1 Productiveness (m2)

DESCRIPTION OF PRODUCT

Prodinex's SPC wall panel is a high-quality, durable option designed for both residential and commercial spaces. It offers the aesthetic appeal of natural materials like wood or stone while being waterproof. SPC wall panels can be installed by applying sealant glue. The wall covering is intended for indoor use in dry conditions.

VISUAL PRODUCT



MORE INFORMATION https://www.prodinex.com/

PROGRAM OPERATOR

Stichting MRPI®

Kingsfordweg 151

1043 GR

Amsterdam

Ing. L. L. Oosterveen MSC. MBA	DEMONSTRATION	OF VERIFICATION
Managing Director MRPI	CEN standard EN15804	serves as the core PCR [1]
	Independent verification	of the declaration an data
	according to	EN15804+A2
/	internal:	external: X
	Third party verifier: Gert-Jan Vroege, E	co-intelligence
Lookur		Voey
	[1] PCR = Product Category Rules	F







DETAILED PRODUCT DESCRIPTION (PART 1)

The manufacturing of the SPC wall panel is almost identical to Prodinex's SPC flooring. However, the SPC wall does not contain an IXPE layer unlike the SPC flooring. The production of the SPC wall starts with mixing the raw materials. The mix is then pressed through a die by means of extrusion. At the same time the decor film and wearlayer are fixed on the SPC board. After the product has cooled down, a UV+PUR coating is applied. The product is cut to size and then packed. The product consists of: Decor film, Wearlayer, UV coating, PVC, Stone powder. The lifespan (RSL) of the wall panels is at least 10 years. Prodinex gives a warranty period of 25 years for domestic use and 10 years for commercial use.

Composition (A1)	Amount per m2 [kg]
Decor film	0,097
Wearlayer	0,005
UV	0,035
PVC	2,325
Stone powder	7,674
Stabilizer	0,046
Plasticizer	0,186

DETAILED PRODUCT DESCRIPTION (PART 2)

Part 1 continued (A1).

Composition (A1) - continued	Amount per m2 [kg]
Toughener	0,233
Lubricant	0,14

DETAILED PRODUCT DESCRIPTION (PART 3)

The production figures above (A1-A3) exclude the use of packaging materials and processing of production waste (duo to edge materials and B grade products). The production loss is calculated at 8,77% for the SPC wall. The losses are either used for other customers or burned at the production site in China.

Use of packaging materials (A3)	Amount per m2
Pallets	0,00975

DETAILED PRODUCT DESCRIPTION (PART 4)

Production requirements: Water, electricity & steam (A3)

Production requirements (A3)	Amount per m2
Water	0,00217 m3
Electricity	3,14 kWh
Steam	3,96 kg

DETAILED PRODUCT DESCRIPTION (PART 5)

Loss at construction site for flooring (5%) and mounting materials (A5)

SPC wall glue (kit) based on Bostik H995 (Polyurethane) (A5)	0,133 kg







SCOPE AND TYPE

Production location: Shandong province, China; Distribution location: Asten, Netherlands; market: Netherlands/ Europe (B2B); End-of-life: Netherlands; Background Database: Ecoinvent 3.9; LCA software: SimaPro; Type of EPD: according to EN15804+A2; EPD: specific.

PRODUCT STAGE			CONSTRUC PROCESS S	TION TAGE			US	ER STA	GE		EN	D OF LI	FE STA	GE	BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES											
Raw material supply	Transport	Aanufacturing	anufacturing	anufacturing	lanufacturing	lanufacturing	1anufacturing	lanufacturing	lanufacturing	Aanufacturing	Vlanufacturing	Vlanufacturing	Transport gate to site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse - Recovery - Recycling potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D										
Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х										

X = Modules Assessed

ND = Not Declared









REPRESENTATIVENESS

This EPD is representative for SPC 5,0/0,3 wall produced by Prodinex in China and distributed in Asten (Netherlands). There is only 1 production site and plant in the Shandong province in China and 1 distribution site in the Netherlands.







ENVIRONMENTAL IMPACT per functional unit or declared unit (indicators A1)

E	enheid	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
ADPE	kg Sb eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
ADPF	MJ	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
GWP	kg CO2 eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
ODP	kg CFC11 eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
POCP	kg ethene eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
AP	kg SO2 eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
EP	kg (PO4) 3- eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
Toxicity	indicato	ors and I	ECI (Du	tch marl	ket)														
HTP	kg DCB eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
FAETP	kg DCB eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
MAETP	kg DCB eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
TETP	kg DCB eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
ECI	euro	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
ADPF	kg Sn eq.	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND

ADPE	=	Abiotic Depletion Potential for non-fossil resources
ADPF	=	Abiotic Depletion Potential for fossil resources
GWP	=	Global Warming Potential
ODP	=	Depletion potential of the stratospheric ozone layer
POCP	=	Formation potential of tropospheric ozone photochemical oxidants
AP	=	Acidification Potential of land and water
EP	=	Eutrophication Potential
HTP	=	Human Toxicity Potential
FAETP	=	Fresh water aquatic ecotoxicity potential
MAETP	=	Marine aquatic ecotoxicity potential
TETP	=	Terrestrial ecotoxicity potential
ECI	=	Environmental Cost Indicator
ADPF	=	Abiotic Depletion Potential for fossil resources







ENVIRONMENTAL IMPACT per functional unit or declared unit (core indicators A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-total	kg CO2 eq	1,00E+01	7,10E-01	4,72E+00	1,55E+01	3,38E+00	1,75E+00	0,00E+00	9,09E-02	2,18E-01	3,95E+00	6,80E+00	-3,46E-01						
GWP-fossil	kg CO2 eq	1,02E+01	7,06E-01	4,73E+00	1,56E+01	3,37E+00	1,71E+00	0,00E+00	8,99E-02	2,17E-01	3,96E+00	6,78E+00	-3,43E-01						
GWP- biogenic	kg CO2 eq	-1,58E-01	1,10E-03	-1,31E-02	-1,70E-01	1,05E-03	3,24E-02	0,00E+00	1,00E-03	3,38E-04	-9,34E-03	2,43E-02	-2,54E-03						
GWP-luluc	kg CO2 eq	2,27E-02	2,52E-03	2,14E-03	2,73E-02	4,41E-03	1,79E-03	0,00E+00	3,40E-05	7,72E-04	2,58E-03	3,37E-03	-1,80E-04						
ODP	kg CFC11 eq	4,35E-06	1,26E-08	1,20E-07	4,48E-06	5,63E-08	2,77E-07	0,00E+00	2,82E-09	3,85E-09	3,75E-08	9,44E-07	-1,27E-07						
AP	mol H+ eq.	5,10E-02	3,38E-03	1,96E-02	7,40E-02	7,06E-02	6,55E-03	0,00E+00	2,08E-04	1,04E-03	1,04E-02	1,14E-02	-9,72E-04						
EP-fresh water	kg PO4 eq.	4,22E-04	7,02E-06	8,32E-05	5,13E-04	1,97E-05	6,21E-05	0,00E+00	3,74E-06	2,15E-06	6,73E-05	9,52E-05	-9,03E-06						
EP-marine	kg N eq.	8,96E-03	1,28E-03	3,79E-03	1,40E-02	1,84E-02	1,37E-03	0,00E+00	4,36E-05	3,94E-04	3,07E-03	2,62E-03	-1,86E-04						
EP- terrestrial	mol N eq.	9,97E-02	1,37E-02	4,16E-02	1,55E-01	2,03E-01	1,44E-02	0,00E+00	5,18E-04	4,20E-03	3,31E-02	2,89E-02	-1,97E-03						
POCP	kg NMVOC eq.	3,85E-02	4,68E-03	1,25E-02	5,57E-02	5,65E-02	5,32E-03	0,00E+00	1,57E-04	1,43E-03	1,25E-02	8,69E-03	-8,59E-04						
ADP- minerals & metals	kg Sb eq.	9,58E-05	2,21E-06	3,80E-06	1,02E-04	5,84E-06	8,52E-06	0,00E+00	8,13E-07	6,78E-07	1,39E-05	1,54E-05	-2,60E-06						
ADP-fossil	MJ, net calorific value	2,03E+02	1,01E+01	4,86E+01	2,62E+02	4,39E+01	2,49E+01	0,00E+00	1,30E+00	3,10E+00	3,89E+01	2,47E+01	-7,70E+00						
WDP	m3 world eq. Deprived	2,06E+00	5,52E-02	6,32E-01	2,74E+00	1,46E-01	6,12E-01	0,00E+00	1,24E-02	1,69E-02	4,84E-01	1,52E+00	-3,81E-01						

GWP-total	=	Global Warming Potential total
GWP-fossil	=	Global Warming Potential fossil fuels
GWP-biogenic	=	Global Warming Potential biogenictotal
GWP-luluc	=	Global Warming Potential land use and land use change
ODP	=	Depletion potential of the stratospheric ozone layer
AP	=	Acidification Potential, Accumulated Exceedence
EP-freshwater	=	Eutrophication Potential, fraction of nutrients reaching freshwater end compartment
EP-marine	=	Eutrophication Potential, fraction of nutrients reaching marine end compartment
EP-terrestrial	=	Eutrophication Potential, Accumulated Exceedence
POCP	=	Formation potential of tropospheric ozone photochemical oxidants
ADP-minerals & metals	=	Abiotic Depletion Potential for non-fossil resources [1]
ADP-fossil	=	Abiotic Depletion for fossil resources potential [1]
WDP	=	Water (user) deprivation potential, deprivation-weighted water consumption [1]

Disclaimer [1]:

- The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.







ENVIRONMENTAL IMPACT per functional unit or declared unit (additional indicators A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
РМ	Disease inci-dence	4,84E-07	6,97E-08	2,60E-07	8,14E-07	1,82E-07	1,05E-07	0,00E+00	9,45E-10	2,14E-08	2,21E-07	1,17E-07	-7,52E-09						
IRP	kBq U235 eq.	3,00E-01	3,95E-03	1,03E-01	4,08E-01	1,32E-02	3,13E-02	0,00E+00	2,98E-03	1,21E-03	4,91E-02	8,24E-02	-1,12E-02						
ETP-fw	CTUe	7,02E+01	7,46E+00	5,18E+01	1,29E+02	2,41E+01	4,71E+01	0,00E+00	2,11E-01	2,29E+00	1,58E+01	3,98E+02	-1,17E+00						
HTP-c	CTUh	7,46E-09	3,74E-10	1,06E-09	8,89E-09	1,58E-09	9,08E-10	0,00E+00	2,98E-11	1,15E-10	3,93E-09	2,34E-09	-1,46E-10						
HTP-nc	CTUh	1,34E-07	8,12E-09	3,36E-08	1,76E-07	2,13E-08	1,63E-08	0,00E+00	1,09E-09	2,49E-09	3,45E-08	4,00E-08	-3,89E-09						
SQP	-	4,79E+01	7,98E+00	6,86E+00	6,28E+01	1,53E+01	5,72E+00	0,00E+00	2,82E-01	2,45E+00	2,86E+01	9,54E+00	-5,67E-01						

PM	=	Potential incidence of disease due to PM emissions
IRP	=	Potential Human exposure efficiency relative to U235 [1]
ETP-fw	=	Potential Comparative Toxic Unit for ecosystems [2]
HTP-c	=	Potential Comparative Toxic Unit for humans [2]
HTP-nc	=	Potential Comparative Toxic Unit for humans, non-cancer [2]
SQP	=	Potential soil quality index [2]

Disclaimer [1]:

- This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle.

It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste.

Disclaimer [2]:

- The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.







OUTPUT FLOWS AND WASTE CATEGORIES per functional unit or declared unit (A1 en A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
HWD	kg	3,99E-04	6,45E-05	1,03E-04	5,67E-04	2,41E-04	4,50E-05	0,00E+00	4,20E-06	1,98E-05	1,38E-04	8,34E-05	-1,72E-05						
NHWD	kg	1,19E+00	6,68E-01	2,64E-01	2,12E+00	1,18E+00	3,11E-01	0,00E+00	4,77E-03	2,05E-01	1,95E+00	1,47E+00	-2,29E-02						
RWD	kg	2,10E-04	2,31E-06	7,64E-05	2,88E-04	7,64E-06	2,24E-05	0,00E+00	2,61E-06	7,10E-07	3,62E-05	5,79E-05	-8,96E-06						
CRU	kg	0,00E+00																	
MFR	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,57E-02	0,00E+00	5,13E-01	0,00E+00	0,00E+00								
MER	kg	0,00E+00																	
EEE	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	6,65E-01	0,00E+00	1,13E+01	0,00E+00									
ETE	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	1,14E+00	0,00E+00	1,95E+01	0,00E+00									

HWD	=	Hazardous Waste Disposed
NHWD	=	Non Hazardous Waste Disposed
RWD	=	Radioactive Waste Disposed
CRU	=	Components for reuse
MFR	=	Materials for recycling
MER	=	Materials for energy recovery
EEE	=	Exported Electrical Energy
ETE	=	Exported Thermal Energy







RESOURCE USE per functional unit or declared unit (A1 and A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PERE	MJ	1,36E+01	1,43E-01	2,08E+00	1,59E+01	4,44E-01	1,43E+00	0,00E+00	2,33E-01	4,38E-02	1,96E+00	2,77E+00	-3,05E-01						
PERM	MJ	0,00E+00																	
PERT	MJ	1,36E+01	1,43E-01	2,08E+00	1,59E+01	4,44E-01	1,43E+00	0,00E+00	2,33E-01	4,38E-02	1,96E+00	2,77E+00	-3,05E-01						
PENRE	MJ	2,03E+02	1,01E+01	4,86E+01	2,62E+02	4,39E+01	2,49E+01	0,00E+00	1,30E+00	3,11E+00	3,89E+01	2,47E+01	-7,70E+00						
PENRM	MJ	0,00E+00																	
PENRT	MJ	2,03E+02	1,01E+01	4,86E+01	2,62E+02	4,39E+01	2,49E+01	0,00E+00	1,30E+00	3,11E+00	3,89E+01	2,47E+01	-7,70E+00						
SM	kg	0,00E+00																	
RSF	MJ	0,00E+00																	
NSRF	MJ	0,00E+00																	
FW	m3	3,67E-02	2,44E-03	1,59E-02	5,51E-02	5,64E-03	1,47E-02	0,00E+00	6,74E-04	7,50E-04	1,46E-02	4,13E-02	-2,92E-03						

PERE	=	Use of renewable energy excluding renewable primary energy resources
PERM	=	Use of renewable energy resources used as raw materials
PERT	=	Total use of renewable primary energy resources
PENRE	=	Use of non-renewable primary energy resources excluding non-renewable energy resources used as raw materials
PENRM	=	Use of non-renewable primary energy resources used as raw materials
PENRT	=	Total use of non-renewable primary energy resources
SM	=	Use of secondary materials
RSF	=	Use of renewable secondary fuels
NSRF	=	Use of non-renewable secondary fuels
FW	=	Use of net fresh water

BIOGENIC CARBON CONTENT per functional unit or declared unit (A1 and A2)

	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
BBCpr	kg C	ND	ND	ND	0,00E+00	ND													
ВССра	kg C	ND	ND	ND	0,00E+00	ND													

BCCpr BCCpa = Biogenic carbon content in product

a = Biogenic carbon content in packaging







CALCULATION RULES (PART 1)

Process data were collected by Prodinex from the production location in China. The data were collected using the questionnaire drawn up by SGS INTRON for the base year 2024. Input and output data were collected for the following data categories:

- Raw materials and processes;
- Energy use;
- Production waste.

The LCA calculations are made using the Ecoinvent database v3.9 Infrastructure processes in Ecoinvent processes have been included, long term emissions in Ecoinvent processes have been excluded from the LCA calculations. The validation of data made available by Prodinex has been validated at process and company level.

Capital goods at the production location have not been specifically investigated for the production location in China and therefore not explicitly included in the LCA study. Within the Ecolnvent/NMD processes, capital goods have been included, for example for the extrusion of PVC. The products on pallets are wrapped in 1-2 layers of PE foil for shipping. This PE foil has not been included in the LCA calculation, because its environmental impact will be <1%. For basic processes, the SimaPro file of the National Environmental Database 3.9 and Ecoinvent 3.9.1 were used. • The environmental interventions were determined using the methods described in the Bepalingsmethode. The LCA calculations were performed in accordance with EN 15804+A2:2019. • When calculating the energy flows, the fuels and electricity sources used, extraction and transport of the fuels, efficiency of the conversion and the distribution of the energy flow were taken into account. The calorific net value (LHV) was also calculated.

• The rules for allocation in multi-input, -output, recycling and reuse processes from the Determination Method were followed for all materials.

SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION (PART 1)

The wall panels will be demolished after use and then taken to certified processors. The waste scenario is considered to be the same for the different types of flooring/ walling: PVC/LVT dryback floor, SPC CLICK floor and SPC walls. The only difference is that the fastening materials (sealant adhesive) are processed separately. For the waste scenario of the LCA, a flat-rate value has been used per type of material. A distinction has been made between 4 different materials: PVC, stone-like material, fastening materials (floor adhesive/ sealant) and (IX)PE for the SPC CLICK floor. All materials that fall within phase A1, except stone powder and IXPE, are considered to be processed as PVC. The fixed value of the determination method (Bepalingsmethode) of 62 for PVC, foils is used for the waste scenario. This scenario states that 10% is dumped, 85% is incinerated and 5% is recycled. The same values are applied for PVC/PE as for stone powder (10% dumped, 85% incinerated and 5% recycled), but different processing processes are used. The waste scenario for stone powder is modelled in the same way as for plastics, but the landfill/incineration processes have been adjusted as stone powder has a lower LHV compared to plastics. It is assumed that the walling adhesive is fully processed together with the product, but as a worst-case scenario, 100% incineration has been assumed for this material. In addition, a processing scenario was used for the packaging materials (cardboard and wooden pallets) in which 100% combustion was assumed. The packaging materials were modelled within module A5, as the material is released on the construction site. For the demolition processes (C1) it is assumed that the demolition labour is done manually and therefore has a value of 0. All material is processed (C3) before being transported and processed at a recycling (5%) or incineration plant (85%) or dumped (10%) (C4). The following LHV's were used: PVC 21,51MJ/kg, Stone powder 0,046MJ/kg*, PE 42,47MJ/kg, PUR/ floor glue and leveling compound 30,67MJ/kg, Pallet (wood) 13,99MJ/kg and Cardboard packaging (boxes) 15,92MJ/kg. For the recycled PVC and PE the production of an equivalent of virgin material is avoided (D). For the burning of the PVC, PE, packaging and mounting materials an equivalent of energy production is avoided (D). The Dutch incenaration values of 18% electric and 31% thermic have been adhered to. *For stone powder only a LHV is used for the C4 process and no benefits for the burning of stone powder (D) are calculated.

Dumping of PVC	5%
Dumping of PE	5%
Dumping of stone powder	5%
Incineration PVC	85%
Incineration PE	85%
Incineration stone powder	85%
Incineration packaging materials: pallets	100%
Incineration packaging materials: cardboard	100%
Incineration mounting material: sealant glue	100%







DECLARATION OF SVHC

No substances that are listed in the latest "Candidate List of Substances of Very High Concern for authorisation" are included in the product that exceeds the limit for registration.

REFERENCES

[1] Nationale Milieudatabase, "Forfaitaire waarden voor verwerking-scenario's einde leven behorende bij: Bepalingsmethode Milieuprestatie Bouwwerken", mei 2024

[2] Nationale Milieudatabase, "Bepalingsmethode Milieuprestatie Bouwwerken", versie 1.2, januari 2025

[3] Nationale Milieudatabase, "NMD-Toetsingsprotocol opname data in de nationale milieudatabase", augustus 2024

[4] EN 15804 (incl. A1:2013 en A2:2019), "Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products"

[5] ISO 14040, "Environmental management - Environmental management -- Life cycle assessment - Principles and framework", ISO14040:2006

[6] ISO 14044, "Environmental management - Life cycle assessment - Requirements and guidelines", ISO14044:2006

[7] International Organization for Standardization, ISO/DIS 21930, "Sustainability in building construction – Environmental declaration of building products", ISO/DIS 21930:2007

[8] International Organization for Standardization, ISO/TR 14025, "Environmental labels and declarations – Type III environmental declarations", ISO/TR 14025:2000

[9] EUROPEAN COMMITTEE FOR STANDARDIZATION, EN 16810:2017, "Resilient, textile and laminate floor coverings - Environmental product declarations - Product category rules"



